

DATA SHEET

October 2006

Product Specification

NORWAX COLOURS

Description

Mixture of special waxes and pigments for pull-up

Appearance

Waxy paste in a range of colours

Activity

100%

Melting point

60-80C (depending on colour)

Storage Stability

3 years

Characteristics

Norwax colours are an exclusive range of colours waxes that assist the masking of defects and help upgrade lower quality leathers. The general requirements for corrected grain is 10-15 parts per mix . For full grain 5-10 parts.

Properties

To obtain a natural appearance with good defect covering properties, Norwax colours should be applied during the first coat followed by a matt plate. Subsequent coats are then applied clear to obtain the best anilinity and fastness.

Application

By heated rollercoater machine. To prevent poor dispersion melt coloured waxes first before blending with Wax/oil mixture.

Storage Behaviour

Not sensitive to cold.

Product code

2-6249

Norwax colour range



Colours shown are reproduced as close as the printing process will allow

All information and data contained herein are believed to be correct. However, this should not be accepted as a guarantee of accuracy.

 **nlc**
LEATHER INDUSTRY SPECIALISTS
Northants Leather Chemicals Ltd
12 North Portway Close, Round Spinney Industrial Estate,
Northampton, NN3 8RQ. United Kingdom.
Tel: +44(0) 1604 647270 Fax: +44(0) 1604 790553